

TECHNICAL DATA SHEET



**PREMIER
LUBRICANTS**
LIQUID ENGINEERS

PREMIER UTTO 10W30

Description

Premier UTTO 10-30 is a multifunctional transmission and hydraulic fluid for tractors and plant. For use in transmission and final drives and suitable for wet brakes, hydraulic and power steering.

Performance Levels

AGCO / ALLIS	Q196, 821 XL
ALLISON	C-4
API	GL-4
CASE	MS 1204, 1205, 1206, 1207, 1209, 1210, 1230
CASE NEW HOLLAND	MAT3505, 3506, 3509, 3525, 3526, 3540
CATERPILLAR	TO-2
DENISON	HF-0, HF-1, HF-2
FORD	M2C 41-B, 48-B & C3, 53-A, 86-B, C, 134-A, 134-B, 134-C, 134-D, FNHA-2-C-200.00, 201.00
JOHN DEERE	J20 A, B, C
KOMATSU	AXO80
KUBOTA	UDT
MASSEY FERGUSON	M1135, 1141, 1143, 1145
NEW HOLLAND	NH 410-B
SFDG	OT 1891-A
VALTRA	G2-08, G2-B10
VICKERS	M230-S, M2950S, I-280-S
VOLVO	WB101
ZF	TE-ML 03E, 05F, 06K, 17E, 21F

SUITABLE FOR USE IN CLAAS, DEUTZ, FENDT, LANDINI, MCCORMICK, RENAULT, SOME-LAMBORGHINI TRANSMISSIONS.

Benefits

- Excellent anti-squawk properties.
- Suitable for nearly all hydraulic, transmission and differential systems.
- Excellent thermal and oxidation stability.

Typical Data

SAE		10W-30
Specific Gravity	@ 15°C	0.860
Kinematic Viscosity	@ 100°C cSt	9.5
	@ 40°C cSt	64
Viscosity Index		130
Pour Point °C		-42°C

Revision Date: January 2025

Dewsbury Road,
Fenton Industrial Estate,
Stoke-on-Trent ST4 2TE
Telephone: 01782 410381