

Technical Data Sheet

STOU 10W/30 Tractor Oil

Description

This is a multipurpose tractor oil meeting all the requirements of the mechanical components of the major manufacturers including 'wet' brakes, hydraulics, gears and transmissions.

The product is developed and tested for the most arduous duties of modern agricultural machinery with the additive package not only approved against the world's two major STOU specifications, Ford and Massey Ferguson, but is also acknowledged by other leading manufacturers.

Performance Levels

Engines

API CG-4
ACEA E3
API SF

Transmission

API: GL4
ZF TE-ML 06A, B, C
ZF TE-ML 07B

Stou

Ford M2C 159B/C
New Holland 82009201/2/3
John Deere J27
Massey Ferguson CMS M1144 and 1139

UTTO

Ford M2C 134D
Case New Holland MAT 3525 and 3526
John Deere J20C
Massey Ferguson CMS M1143 and 1135

Benefits

- This is a high quality Multigrade and functional product.
- Top quality specification for both diesel and petrol engines whether turbo charged or naturally aspirated.
- Outstanding hydraulic filterability and stability in the presence of water.
- Excellent oxidation and thermal stability.

Typical Data

SAE		10W/30
Specific Gravity	@ 15°C cSt	0.884
Kinematic Viscosity	@ 100°C cSt	10.7
	@ 40°C cSt	61.0
Viscosity Index		160
Pour Point (°C)		-30
TBN (mg KOH/gram)		15

Little Row, Fenton Industrial Estate
Stoke on Trent, Staffordshire ST4 2SQ

Telephone 01782410381 / 410389
Fax. 01782 410684

Email.sales@premierlubricants.co.uk
www.premierlubricants.co.uk