

Fitting instruction for 300-200P Lift Pump

These instructions refer to fitting to Morris Lubricants 25 litre drums with the Berg closure.

Unscrew the cap from the drum, underneath there will be a plastic ring pull.

Remove the ring pull & pull up & remove the pouring spout, some resistance will be felt at the end give it a sharp tug or wiggle & it will come out. You don't need this when using the pump so it can be discarded or saved if you wish.

On the pump is a black adapter, screw this onto the drum, it should be self-evident which end goes on, but it is the narrower end with the male protrusion. It is a small thread so do not over tighten, finger tight is sufficient.

Slide the pump into the adapter ensuring the downspout reaches the bottom of the drum.

Screw the Red locater into the Black adapter and secure with locking nut. Do not over tighten!

Fit the delivery spout to the aperture at the top of the pump & you are ready to go.

Pump the handle up & down using a smooth vertical motion when pumping & don't twist sideways or the unit may snap off the drum.

***NOTE**

***THIS PUMP IS DESIGNED TO BE USED & STORED WITH THE DRUM IN AN UPRIGHT POSITION, DO NOT PLACE THE DRUM ON IT'S SIDE ON A SHELF OR STILLAGE AS THE PUMP WILL NOT MAKE A SEAL AND THE PRODUCT WILL LEAK OUT.**

