according to Regulation (EC) No. 1907/2006

PURITY [™] FG2 SYNTHETIC





SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

: PURITY [™] FG2 SYNTHETIC Product name

: PFGSYN2P17, PFGSYN2KGL, PFGSYN2DRL, PFGSYN2, Product code

PFGSYN2C30

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Purity FG2 Synthetic grease is a food grade lubricant.

Substance/Mixture

NSF H1 Registered.

All components comply with FDA 21 CFR 178.3570

"Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be

added directly to the food product.

1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

Petro-Canada Europe Lubricants Limited

Wellington House, Starley Way

Birmingham International Park Solihull B37 7HB

United Kingdom

E-mail address of person

responsible for the SDS

: EUSDS@suncor.com

1.4 Emergency telephone number

Emergency telephone

Suncor Energy: +1 403-296-3000;

number

Poison Control Centre: Consult local telephone directory for

emergency number(s).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)


Eye irritation, Category 2 H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction. Skin sensitisation, Category 1

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.

TM Trademark of Suncor Energy Inc. Used under licence.







according to Regulation (EC) No. 1907/2006

PURITY ™ FG2 SYNTHETIC



Version 2.0 Revision Date 2015/04/02

Print Date 2015/04/02

Classification (67/548/EEC, 1999/45/EC)

Sensitising R43: May cause sensitisation by skin contact.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

 \Diamond

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**

P261 Avoid breathing dust/ fume/ gas/ mist/

vapours/ spray.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Hazardous components which must be listed on the label:

Sulfonic acids, petroleum, calcium salts

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No.	Classification	Classification	Concentration
	EC-No.	(67/548/EEC)	(REGULATION	(%)
	Registration		(EC) No	
	number		1272/2008)	
Sulfonic acids,	61789-86-4	R43	Skin Sens. 1B;	1 - 10
petroleum, calcium			H317	
salts	263-093-9			

according to Regulation (EC) No. 1907/2006

PURITY TM FG2 SYNTHETIC



Version 2.0



Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	68584-23-6 271-529-4	R43	Skin Sens. 1B; H317	1 - 10
Benzenamine, N- phenyl-, reaction products with 2,4,4- trimethylpentene	68411-46-1 270-128-1	R52/53	Aquatic Chronic 3; H412	1 - 10
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0 274-263-7	R43	Skin Sens. 1B; H317	1 - 10
calcium dodecylbenzenesulpho nate	26264-06-2 247-557-8	Xi; R38-R41	Skin irr/cor. 2; H315 Eye irr/damage 1; H318	1 - 3

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In the event of a known, or potential, high pressure injection injury, worker should obtain immediate medical evaluation.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a


physician or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Risks : First aider needs to protect himself.



Page: 3 / 11

according to Regulation (EC) No. 1907/2006

PURITY [™]FG2 SYNTHETIC





4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: No information available.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Cool closed containers exposed to fire with water spray.

Hazardous combustion

products

: Carbon oxides (CO, CO2), smoke and irritating vapours as

products of incomplete combustion.

5.3 Advice for firefighters

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the

environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material.

Non-sparking tools should be used.

Ensure adequate ventilation.

Contact the proper local authorities.

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.

according to Regulation (EC) No. 1907/2006

PURITY [™] FG2 SYNTHETIC







6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Use only with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Advice on protection against

fire and explosion

: None known.

Hygiene measures : Remove and wash contaminated clothing and gloves,

including the inside, before re-use. Wash face, hands and any

exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store

in heat or direct sunlight.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

according to Regulation (EC) No. 1907/2006

PURITY ™ FG2 SYNTHETIC



Version 2.0 Revision Date 2015/04/02 Print Date 2015/04/02

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Protective measures : Wash contaminated clothing before re-use.

No special protective equipment required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Semi-solid.

Colour : Cream.

Odour : Mild petroleum oil like.

Odour Threshold : No data available
pH : No data available
Pour point : -63 °C (-81 °F)
Boiling point/boiling range : No data available

Flash point : 252 °C (486 °F)

Method: Cleveland open cup

Fire Point : 286 °C (547 °F)

Auto-Ignition Temperature : No data available Evaporation rate : No data available

Flammability (solid, gas) : Low fire hazard. This material must be heated before ignition

will occur.

Upper explosion limit : No data available

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.

according to Regulation (EC) No. 1907/2006

PURITY THE FG2 SYNTHETIC



Version 2.0 Revision Date 2015/04/02 Print Date 2015/04/02

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.832 kg/l (15 °C / 59 °F)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, kinematic : 50.0 cSt (40 °C / 104 °F)

7.80 cSt (100 °C / 212 °F)

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

Stable under normal conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents.


10.6 Hazardous decomposition products

Hazardous decomposition

products

: May release COx, SOx, CaOx, smoke and irritating vapours

when heated to decomposition.



according to Regulation (EC) No. 1907/2006

PURITY TM FG2 SYNTHETIC



Version 2.0 Revision Date 2015/04/02



Print Date 2015/04/02

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Eye contact

exposure

Ingestion
Inhalation
Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Product:

Remarks: No data available

Serious eye damage/eye irritation

Product:

Remarks: No data available

Remarks: No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

according to Regulation (EC) No. 1907/2006

PURITY TM FG2 SYNTHETIC



Version 2.0 Revision Date 2015/04/02 Print Date 2015/04/02

No data available

Aspiration toxicity

No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

: Remarks: No data available Toxicity to fish

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

: Remarks: No data available Toxicity to algae

Toxicity to bacteria

Remarks: No data available

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.

™ Trademark of Suncor Energy Inc. Used under licence.

Page: 9 / 11



according to Regulation (EC) No. 1907/2006

PURITY [™] FG2 SYNTHETIC





national regulations.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14: Transport information

International Regulation

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

49 CFR

Not regulated as a dangerous good

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water contaminating class

(Germany)

: WGK 2 water endangering

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory


exemption.

AICS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory



Page: 10 / 11

according to Regulation (EC) No. 1907/2006

PURITY ™ FG2 SYNTHETIC





Version 2.0 Revision Date 2015/04/02 Print Date 2015/04/02

NZIoC : On the inventory, or in compliance with the inventory

EINECS : On the inventory, or in compliance with the inventory

15.2 Chemical Safety Assessment

SECTION 16: Other information

Full text of R-Phrases

R38 : Irritating to skin.

R41 : Risk of serious damage to eyes.

R43 : May cause sensitisation by skin contact.

R52/53 : Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

Full text of H-Statements

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity

Eve irr/damage : Serious eve damage/eve irritation

Skin irr/cor. : Skin corrosion/irritation Skin Sens. : Skin sensitisation

For Copy of (M)SDS : Internet: lubricants.petro-canada.ca/msds

Europe, telephone: 00-800-7387-6000

For Product Safety Information: 1 905-804-4752

Prepared by : Product Safety: +1 905-804-4752

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.