

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY™ FG AW HYDRAULIC FLUID 32

000003000529



Version 2.0

Revision Date 2015/02/18

Print Date 2015/02/18

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : PURITY™ FG AW HYDRAULIC FLUID 32

Product code : PFAW32P20, PFAW32IBC, PFAW32, PFAW32DRX

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : PURITY FG AW Hydraulic Fluid are food grade hydraulic fluids and light gear oils.

NSF H1 Registered.

All components comply with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added directly to the food product.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

Petro-Canada Europe Lubricants Limited  
Wellington House, Starley Way  
Birmingham International Park Solihull B37 7HB  
United Kingdom

E-mail address of person responsible for the SDS : EUSDS@suncor.com

#### 1.4 Emergency telephone number

Emergency telephone number : Suncor Energy: +1 403-296-3000;  
Poison Control Centre: Consult local telephone directory for emergency number(s).

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting effects.

##### Classification (67/548/EEC, 1999/45/EC)

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**PURITY™ FG AW HYDRAULIC FLUID 32**



000003000529

Version 2.0

Revision Date 2015/02/18

Print Date 2015/02/18

Dangerous for the environment

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P273 Avoid release to the environment.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Other hazards

None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

| Chemical Name              | CAS-No.<br>EC-No.<br>Registration<br>number | Classification<br>(67/548/EEC) | Classification<br>(REGULATION<br>(EC) No<br>1272/2008) | Concentration<br>(%) |
|----------------------------|---|--------------------------------|--|----------------------|
| 2,6-di-tert-butyl-p-cresol | 128-37-0<br><br>204-881-4                   | R50/53                         | Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410 | 0.25 - 1             |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

If inhaled : Move to fresh air.  
Artificial respiration and/or oxygen may be necessary.  
Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash skin thoroughly with soap and water or use recognized

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY™ FG AW HYDRAULIC FLUID 32



000003000529

Version 2.0

Revision Date 2015/02/18

Print Date 2015/02/18

- skin cleanser.  
Wash clothing before reuse.  
Seek medical advice.
- In case of eye contact : Remove contact lenses.  
Rinse immediately with plenty of water, also under the eyelids,  
for at least 15 minutes.  
Obtain medical attention.
- If swallowed : Rinse mouth with water.  
DO NOT induce vomiting unless directed to do so by a  
physician or poison control center.  
Never give anything by mouth to an unconscious person.  
Seek medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : First aider needs to protect himself.

### 4.3 Indication of any immediate medical attention and special treatment needed

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local  
circumstances and the surrounding environment.
- Unsuitable extinguishing media : No information available.

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Cool closed containers exposed to fire with water spray.
- Hazardous combustion products : Carbon oxides (CO, CO<sub>2</sub>), nitrogen oxides (NO<sub>x</sub>), phosphorus  
oxides (PO<sub>x</sub>), smoke and irritating vapours as products of  
incomplete combustion.

### 5.3 Advice for firefighters

- Further information : Prevent fire extinguishing water from contaminating surface  
water or the ground water system.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY™ FG AW HYDRAULIC FLUID 32

000003000529



Version 2.0

Revision Date 2015/02/18

Print Date 2015/02/18

Evacuate personnel to safe areas.  
Material can create slippery conditions.  
Mark the contaminated area with signs and prevent access to unauthorized personnel.  
Only qualified personnel equipped with suitable protective equipment may intervene.

### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Prevent further leakage or spillage if safe to do so.  
Remove all sources of ignition.  
Soak up with inert absorbent material.  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Contact the proper local authorities.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Use only with adequate ventilation.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin, eyes and clothing.  
Do not ingest.  
Keep away from heat and sources of ignition.  
Keep container closed when not in use.

Advice on protection against fire and explosion : None known.

Hygiene measures : Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**PURITY™ FG AW HYDRAULIC FLUID 32**



000003000529

Version 2.0

Revision Date 2015/02/18

Print Date 2015/02/18

in heat or direct sunlight.

### 7.3 Specific end use(s)

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

### 8.2 Exposure controls

#### Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Personal protective equipment

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Skin and body protection

: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection

: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter type

: organic vapour filter

Protective measures

: Wash contaminated clothing before re-use.  
No special protective equipment required.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : viscous liquid

Colour : colourless

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY™ FG AW HYDRAULIC FLUID 32



000003000529

Version 2.0

Revision Date 2015/02/18

Print Date 2015/02/18

|  |  |
|--|--|
| Odour                                  | : Mild petroleum oil like.   |
| Odour Threshold                        | : No data available  |
| pH                                     | : No data available  |
| Pour point                             | : -18 °C (-0.40 °F)  |
| Boiling point/boiling range            | : No data available  |
| Flash point                            | : 225 °C (437 °F)<br>Method: Cleveland open cup  |
| Fire Point                             | : No data available  |
| Auto-Ignition Temperature              | : No data available  |
| Evaporation rate                       | : No data available  |
| Flammability (solid, gas)              | : Low fire hazard. This material must be heated before ignition will occur.                                      |
| Upper explosion limit                  | : No data available  |
| Lower explosion limit                  | : No data available  |
| Vapour pressure                        | : No data available  |
| Relative vapour density                | : No data available  |
| Density                                | : 0.8629 kg/l (15 °C / 59 °F)  |
| Solubility(ies)                        |  |
| Water solubility                       | : insoluble  |
| Partition coefficient: n-octanol/water | : No data available  |
| Viscosity                              |  |
| Viscosity, kinematic                   | : 29.8 cSt (40 °C / 104 °F)<br><br>5.2 cSt (100 °C / 212 °F)   |
| Explosive properties                   | : Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. |

### 9.2 Other information

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY™ FG AW HYDRAULIC FLUID 32



000003000529

Version 2.0

Revision Date 2015/02/18

Print Date 2015/02/18

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

#### 10.2 Chemical stability

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.  
Stable under normal conditions.

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

#### 10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents, acids and alkalis.

#### 10.6 Hazardous decomposition products

Hazardous decomposition products : May release COx, NOx, SOx, POx, SiOx, formaldehyde, smoke and irritating vapours when heated to decomposition.

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Information on likely routes of exposure : Eye contact  
Ingestion  
Inhalation  
Skin contact

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

#### Skin corrosion/irritation

##### Product:

Remarks: No data available

#### Serious eye damage/eye irritation

SAFETY DATA SHEET  
according to Regulation (EC) No. 1907/2006  
**PURITY™ FG AW HYDRAULIC FLUID 32**



000003000529

Version 2.0

Revision Date 2015/02/18

Print Date 2015/02/18

**Product:**

Remarks: No data available

**Respiratory or skin sensitisation**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae : Remarks: No data available

Toxicity to bacteria :  
Remarks: No data available

**12.2 Persistence and degradability**

**Product:**

Biodegradability : Remarks: No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY™ FG AW HYDRAULIC FLUID 32



000003000529

Version 2.0

Revision Date 2015/02/18

Print Date 2015/02/18

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of as hazardous waste in compliance with local and national regulations.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

---

## SECTION 14: Transport information

### International Regulation

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### 49 CFR

Not regulated as a dangerous good

#### TDG

Not regulated as a dangerous good

### Special precautions for user

Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## PURITY™ FG AW HYDRAULIC FLUID 32

000003000529



Version 2.0

Revision Date 2015/02/18

Print Date 2015/02/18

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water contaminating class : WGK 1 slightly water endangering  
(Germany)

##### The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

IECSC : On the inventory, or in compliance with the inventory

EINECS : On the inventory, or in compliance with the inventory

#### 15.2 Chemical Safety Assessment

---

### SECTION 16: Other information

#### Full text of R-Phrases

R50/53 : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### Full text of H-Statements

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Acute : Acute aquatic toxicity

Aquatic Chronic : Chronic aquatic toxicity

For Copy of (M)SDS : Internet: [lubricants.petro-canada.ca/msds](http://lubricants.petro-canada.ca/msds)  
Europe, telephone: 00-800-7387-6000  
For Product Safety Information: 1 905-804-4752

Prepared by : Product Safety: +1 905-804-4752

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## **PURITY™ FG AW HYDRAULIC FLUID 32**



**000003000529**

Version 2.0

Revision Date 2015/02/18

Print Date 2015/02/18

---