

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PREMIERCUT GP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC25: Metal working fluids.

1.3. Details of the supplier of the safety data sheet

Company name: Premier Lubricants Ltd

Little Row

Fenton Ind Estate

Stoke-on-Trent

ST4 2SQ

Tel: +44 1782 410381

Fax: +44 1782 410684

Email: info@premierlubricants.co.uk

1.4. Emergency telephone number

Tel: +44 1782 410381

Opening Hours: 09:00 – 17:00

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319

Most important adverse effects: Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H319: Causes serious eye irritation.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



Precautionary statements: P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

SAFETY DATA SHEET

PREMIERCUT GP

Page: 2

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SULFONIC ACIDS, PETROLEUM, SODIUM SALTS - REACH registered number(s): 01-2119527859-22-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
271-781-5	68608-26-4	-	Eye Irrit. 2: H319	1-10%

ISOTRIDECANOL, ETHOXYLATED

-	69011-36-5	-	Eye Dam. 1: H318; Skin Irrit. 2: H315	1-10%
---	------------	---	---------------------------------------	-------

2,2'-OXYBISETHANOL - REACH registered number(s): 01-2119457857-21

203-872-2	111-46-6	-	Acute Tox. 4: H302	1-10%
-----------	----------	---	--------------------	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Occasional contact with undiluted product is unlikely to cause any significant reaction. Prolonged contact with undiluted product may cause defatting of skin barrier, leading to cracking and soreness.

Eye contact: Eye contact with undiluted product may cause moderate irritation and stinging. There may be a potential to cause corneal injury if treatment is not prompt. Dilute emulsions are expected to cause only slight transient irritation or redness.

Ingestion: The product has a low order of acute oral toxicity; ingestion is not regarded as a significant hazard likely to arise in normal use.

Inhalation: The product is unlikely to present any significant hazard at ambient temperatures. High temperatures or atomising systems may lead to generation of vapours, mists or fumes which could cause irritation to eyes and respiratory tract. Repeated excessive exposure to oil mists may cause respiratory damage and a condition resembling pneumonia.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure. Delayed effects can be expected after long-term exposure.

[cont...]

SAFETY DATA SHEET

PREMIERCUT GP

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in dry conditions between 0 and 40 °C.

7.3. Specific end use(s)

Specific end use(s): PC25: Metal working fluids.

Section 8: Exposure controls/personal protection

[cont...]

SAFETY DATA SHEET

PREMIERCUT GP

Page: 4

8.1. Control parameters

Hazardous ingredients:

2,2'-OXYBISETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	101	-	-	-

DNEL/PNEC Values

Hazardous ingredients:

ISOTRIDECANOL, ETHOXYLATED

Type	Exposure	Value	Population	Effect
PNEC	Fresh water	0.074mg/l	-	-
PNEC	Marine water	0.0074mg/l	-	-
PNEC	Intermittent release	0.015mg/l	-	-
PNEC	STP	1.4mg/l	-	-
PNEC	Fresh water sediments	0.604mg/kg	-	-
PNEC	Marine sediments	0.0604mg/kg	-	-
PNEC	Soil	0.1mg/kg	-	-
DNEL	Inhalation	294mg/m3	Workers	Systemic
DNEL	Dermal	2080mg/kg	Workers	Systemic
DNEL	Inhalation	87mg/m3	Consumers	Systemic
DNEL	Dermal	1250mg/kg	Consumers	Systemic
DNEL	Oral	25mg/kg	Consumers	Systemic

2,2'-OXYBISETHANOL

Type	Exposure	Value	Population	Effect
DNEL	Dermal	53/mg/kg/day	Workers	-
DNEL	Inhalation	12/mg/m3	Workers	-
PNEC	Fresh water	10mg/l	-	-
PNEC	Marine water	1mg/l	-	-
PNEC	Sediment	20.9mg/kg	-	-
PNEC	Soil	1.53mg/kg	-	-
PNEC	STP	10mg/l	-	-

8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Wear oil impervious gloves when handling undiluted product. Prolonged or repeated contact with diluted metalworking fluid is often unavoidable, in such circumstances; the use of barrier and after work creams may be beneficial.

[cont...]

SAFETY DATA SHEET

PREMIERCUT GP

Page: 5

Eye protection: Safety goggles. Face-shield. Ensure eye bath is to hand.

Skin protection: Oil-resistant protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-green

Odour: Barely perceptible odour

Solubility in water: Miscible

Viscosity: Viscous

Kinematic viscosity: 100-200

Viscosity test method: Kinematic viscosity in 10⁻⁶ m²/s at 40°C (ISO 3219)

Boiling point/range°C: >100

Flash point°C: >100

Autoflammability°C: No data available.

Relative density: 1.01

pH: 9.0-9.4

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

[cont...]

SAFETY DATA SHEET

PREMIERCUT GP

Page: 6

Hazardous ingredients:

ISOTRIDECANOL, ETHOXYLATED

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

2,2'-OXYBISETHANOL

ORAL	MUS	FERTILITY	3060	mg/kg
ORAL	RAT	NOAEL	100	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Occasional contact with undiluted product is unlikely to cause any significant reaction.

Prolonged contact with undiluted product may cause defatting of skin barrier, leading to cracking and soreness.

Eye contact: Eye contact with undiluted product may cause moderate irritation and stinging. There may be a potential to cause corneal injury if treatment is not prompt. Dilute emulsions are expected to cause only slight transient irritation or redness.

Ingestion: The product has a low order of acute oral toxicity; ingestion is not regarded as a significant hazard likely to arise in normal use.

Inhalation: The product is unlikely to present any significant hazard at ambient temperatures. High temperatures or atomising systems may lead to generation of vapours, mists or fumes which could cause irritation to eyes and respiratory tract. Repeated excessive exposure to oil mists may cause respiratory damage and a condition resembling pneumonia.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure. Delayed effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ISOTRIDECANOL, ETHOXYLATED

ALGAE	72H EC50	>1-10	mg/l
DAPHNIA	48H EC50	>1-10	mg/l
FISH	96H LC50	>1-10	mg/l

[cont...]

SAFETY DATA SHEET

PREMIERCUT GP

Page: 7

2,2'-OXYBISETHANOL

ALGAE	72H IC50	2700	mg/l
Daphnia magna	48H EC50	>10000	mg/l
FISH (Flat-head Minnow)	96H LC50	75200	mg/l
Mircoorganisms (Activated sludge)	EC20 30mins	>1995	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

[cont...]

SAFETY DATA SHEET

PREMIERCUT GP

Page: 8

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.