

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier****Product name:** PREMIERCUT X7 SEMI SYNTHETIC**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of substance / mixture:** PC25: Metal working fluids.**1.3. Details of the supplier of the safety data sheet****Company name:** Premier Lubricants Ltd

Little Row

Fenton Ind Estate

Stoke-on-Trent

ST4 2SQ

Tel: +44 1782 410381**Fax:** +44 1782 410684**Email:** info@premierlubricants.co.uk**1.4. Emergency telephone number****Tel:** +44 1782 410381**Opening Hours:** 09:00 – 17:00**Section 2: Hazards identification****2.1. Classification of the substance or mixture****Classification under CLP:** Eye Irrit. 2: H319**Most important adverse effects:** Causes serious eye irritation.**2.2. Label elements****Label elements:****Hazard statements:** H319: Causes serious eye irritation.**Signal words:** Warning**Hazard pictograms:** GHS07: Exclamation mark**Precautionary statements:** P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients
3.2. Mixtures
Hazardous ingredients:

SULFONIC ACIDS, PETROLEUM, SODIUM SALTS - REACH registered number(s): 01-2119527859-22-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
271-781-5	68608-26-4	-	Eye Irrit. 2: H319	1-10%

ISOTRIDECANOL, ETHOXYLATED

-	69011-36-5	-	Eye Dam. 1: H318; Skin Irrit. 2: H315	1-10%
---	------------	---	---------------------------------------	-------

2,2'-OXYBISETHANOL - REACH registered number(s): 01-2119457857-21

203-872-2	111-46-6	-	Acute Tox. 4: H302	1-10%
-----------	----------	---	--------------------	-------

Section 4: First aid measures
4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. If irritation persists, obtain medical advice.

Eye contact: Bathe the eye with running water for 15 minutes. For contact with undiluted fluid, obtain prompt medical attention. For contact with diluted fluid, obtain medical attention if irritation persists.

Ingestion: Do not induce vomiting. Wash out mouth with water and obtain medical attention. Treat symptomatically. If aspiration is suspected, obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Occasional contact with undiluted product is unlikely to cause any significant reaction. Prolonged contact with undiluted product may cause defatting of skin barrier, leading to cracking and soreness.

Eye contact: Eye contact with undiluted product may cause moderate irritation and stinging. There may be a potential to cause corneal injury if treatment is not prompt. Dilute emulsions are expected to cause only slight transient irritation or redness.

Ingestion: The product has a low order of acute oral toxicity; ingestion is not regarded as a significant hazard likely to arise in normal use.

Inhalation: The product is unlikely to present any significant hazard at ambient temperatures. High temperatures or atomising systems may lead to generation of vapours, mists or fumes which could cause irritation to eyes and respiratory tract. Repeated excessive exposure to oil mists may cause respiratory damage and a condition resembling pneumonia.

SAFETY DATA SHEET

SEMI SYNTH X7

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: For pressure injection always obtain immediate medical attention. Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Dry chemical powder. Alcohol resistant foam. Carbon dioxide. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in dry conditions between 0 and 40 °C.

7.3. Specific end use(s)

Specific end use(s): PC25: Metal working fluids.

[cont...]

SAFETY DATA SHEET

SEMI SYNTH X7

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2,2'-OXYBISETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	101	-	-	-

DNEL/PNEC Values

Hazardous ingredients:

ISOTRIDECANOL, ETHOXYLATED

Type	Exposure	Value	Population	Effect
PNEC	Fresh water	0.074mg/l	-	-
PNEC	Marine water	0.0074mg/l	-	-
PNEC	Intermittent release	0.015mg/l	-	-
PNEC	STP	1.4mg/l	-	-
PNEC	Fresh water sediments	0.604mg/kg	-	-
PNEC	Marine sediments	0.0604mg/kg	-	-
PNEC	Soil	0.1mg/kg	-	-
DNEL	Inhalation	294mg/m3	Workers	Systemic
DNEL	Dermal	2080mg/kg	Workers	Systemic
DNEL	Inhalation	87mg/m3	Consumers	Systemic
DNEL	Dermal	1250mg/kg	Consumers	Systemic
DNEL	Oral	25mg/kg	Consumers	Systemic

2,2'-OXYBISETHANOL

Type	Exposure	Value	Population	Effect
DNEL	Dermal	53/mg/kg/day	Workers	-
DNEL	Inhalation	12/mg/m3	Workers	-
PNEC	Fresh water	10mg/l	-	-
PNEC	Marine water	1mg/l	-	-
PNEC	Sediment	20.9mg/kg	-	-
PNEC	Soil	1.53mg/kg	-	-
PNEC	STP	10mg/l	-	-

8.2. Exposure controls

Engineering measures: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Respiratory protection: Respiratory protection not required.

Hand protection: Wear oil impervious gloves when handling undiluted product. Prolonged or repeated

[cont...]

SAFETY DATA SHEET

SEMI SYNTH X7

Page: 5

contact with diluted metalworking fluid is often unavoidable, in such circumstances; the use of barrier and after work creams may be beneficial.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Oil-resistant protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Green-blue

Odour: Barely perceptible odour

Solubility in water: Miscible

Viscosity: Non-viscous

Kinematic viscosity: 150-300

Viscosity test method: Kinematic viscosity in 10⁻⁶ m²/s at 40 °C (ISO 3219)

Boiling point/range °C: >100

Melting point/range °C: <0

Flash point °C: >100

Autoflammability °C: No data available.

Relative density: 1.05

pH: 9.0-9.4

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Extremes of temperature. Store between 0 and 40 °C.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: Thermal decomposition can produce various compounds, depending on the conditions in which decomposition took place. Depending on the temperature and the level of oxygen available products of decomposition may be carbon, oxides of sulphur, carbon and nitrogen, partially oxidised organic compounds, water and other unidentifiable organic and inorganic compounds.

[cont...]

SAFETY DATA SHEET

SEMI SYNTH X7

Page: 6

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ISOTRIDECANOL, ETHOXYLATED

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

2,2'-OXYBISETHANOL

ORAL	MUS	FERTILITY	3060	mg/kg
ORAL	RAT	NOAEL	100	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Occasional contact with undiluted product is unlikely to cause any significant reaction.

Prolonged contact with undiluted product may cause defatting of skin barrier, leading to cracking and soreness.

Eye contact: Eye contact with undiluted product may cause moderate irritation and stinging. There may be a potential to cause corneal injury if treatment is not prompt. Dilute emulsions are expected to cause only slight transient irritation or redness.

Ingestion: The product has a low order of acute oral toxicity; ingestion is not regarded as a significant hazard likely to arise in normal use.

Inhalation: The product is unlikely to present any significant hazard at ambient temperatures. High temperatures or atomising systems may lead to generation of vapours, mists or fumes which could cause irritation to eyes and respiratory tract. Repeated excessive exposure to oil mists may cause respiratory damage and a condition resembling pneumonia.

Other information: Aspiration into the lungs caused by vomiting following ingestion can be hazardous with possible resultant chemically induced pneumonia

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET

SEMI SYNTH X7

Page: 7

ISOTRIDECANOL, ETHOXYLATED

ALGAE	72H EC50	>1-10	mg/l
DAPHNIA	48H EC50	>1-10	mg/l
FISH	96H LC50	>1-10	mg/l

2,2'-OXYBISETHANOL

ALGAE	72H IC50	2700	mg/l
Daphnia magna	48H EC50	>10000	mg/l
FISH (Flat-head Minnow)	96H LC50	75200	mg/l
Mircoorganisms (Activated sludge)	EC20 30mins	>1995	mg/l

12.2. Persistence and degradability

Persistence and degradability: The individual components range from readily to poorly biodegradable. Mineral oil itself has limited biodegradability when tested by method CEC L-33-T-82.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Small quantities will be absorbed in the upper soil layers where biodegradation may take place.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Components are not expected to be highly toxic to aquatic life. If released to water product may deplete the oxygen supply to bottom dwelling organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

[cont...]

SAFETY DATA SHEET

SEMI SYNTH X7

Page: 8

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.