

Technical Data Sheet

Premier STOU 15W/30

Description

Premier STOU 15W/30 is a multipurpose tractor oil manufactured from high quality base oils and additives meeting all the requirements of the mechanical components of the major manufacturers including 'wet' brakes, hydraulics, gears and transmissions.

The product is developed and tested for the most arduous duties of modern agricultural machinery with the additive package against the world's two major STOU specifications, Ford and Massey Ferguson, but is also acknowledged by other leading manufacturers.

Performance Levels

ENGINES

API: CF, CF-4, SF

STOU

Ford M2C 159 B/C

New Holland: 82009201/2/3

Massey Ferguson CMS M1139/M1144

TRANSMISSIONS

API: GL4

ZF TE-ML 06B/07B

Allison C4

John Deere: J20C

Massey Ferguson CMS M135/M1143

Ford: M2C 134D

Benefits

- Multigrade and multifunctional.
- Rationalisation of grades.
- Additive package giving excellent oxidation and thermal stability.
- Excellent low-temperature flow characteristics, providing superior cold-start protection.
- Anti-'squawk'.
- Enhanced gear wear protection.
- Advanced hydraulic pump performance.

Typical Data

SAE		15W/30
Specific Gravity	@ 15°C cSt	0.885
Kinematic Viscosity	@ 100°C cSt	10.8
	@ 40°C cSt	78.50
Viscosity Index		125
Flash Point (Closed Cup) °C		200
Pour Point (°C)		-37
TBN (mg KOH/gram)		10.2