

## Product Information

# LIQUIMATIC CH – 5 TRANSMISSION OIL

---

## Description

Liquimatic CH - 5 is a synthetic based automotive transmission fluid, for transmissions requiring Dextron III, Mercon V® and Chrysler4 fluids.

## Applications

Liquimatic CH - 5 is recommended for use in automatic transmissions of most passenger cars, buses, off-highway / construction and military equipment as well as in selected manual transmissions. Liquimatic CH – 5 can also be used as a power steering fluid, or in certain hydraulic applications.

## Performance Levels

**Suitable for use against the following performance levels**

General Motors Dexron III H revised  
Ford Mercon®, Mercon V®  
Daimler Chrysler (Chrysler ATF + 4)  
Voith H.55.6335.3X for standard drain intervals  
ZF TE-ML 14B  
ZF TE-ML 16L  
ZF TE-ML 17C  
MAN 339 Typ F  
Allison C-4  
Volvo 97340

## Benefits

- Extended drain intervals possible due to excellent oxidation stability
- Better low temperature fluidity
- Superior oxidation and thermal stability control
- Advanced wear control
- Improved friction retention

## Physical Characteristics

Appearance	Red
Density at 15 °C	0.852
Viscosity at 100 °C, cSt.	7.8
Viscosity at 40 °C, cSt.	33.5
Viscosity Index	185
Flash Point (Closed) °C	195
Pour Point, °C	-45