

# SAFETY DATA SHEET

## PURITY™ FG COMPRESSOR FLUID 46

000003000431



Version 2.0

Revision Date 2018/07/23

Print Date 2018/07/23

### SECTION 1. IDENTIFICATION

Product name : PURITY™ FG COMPRESSOR FLUID 46

Product code : PFCO46P20, PFCO46, PFCO46DRX

Manufacturer or supplier's details

Petro-Canada Lubricants Inc.  
2310 Lakeshore Road West  
Mississauga ON L5J 1K2  
Canada

Emergency telephone number

Petro-Canada Lubricants Inc.: +1 905-403-5770;  
CHEMTREC Transport Emergency: 1-800-424-9300;  
Poison Control Centre: Consult local telephone directory for emergency number(s).

#### Recommended use of the chemical and restrictions on use

Recommended use : PURITY FG COMPRESSOR FLUID 46 is a new and improved food grade compressor fluid. NSF H1 Registered. All components comply with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added directly to the food product. This compressor oil should NEVER be used in equipment compressing pure oxygen or other chemically active gases such as chlorine or hydrogen chloride. DO NOT USE in breathing air apparatus or medical equipment.

Prepared by : Product Safety: +1 905-491-0565

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	viscous liquid
Colour	colourless
Odour	Mild petroleum oil like.

#### GHS Classification

Not a hazardous substance or mixture.

#### GHS label elements

Not a hazardous substance or mixture.

#### Potential Health Effects

Primary Routes of Entry : Eye contact

# SAFETY DATA SHEET

## PURITY™ FG COMPRESSOR FLUID 46

000003000431



Version 2.0

Revision Date 2018/07/23

Print Date 2018/07/23

Ingestion  
Inhalation  
Skin contact

Aggravated Medical Condition : None known.

### Other hazards

None known.

### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

### ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration
White mineral oil (petroleum)	8042-47-5	90 - 100 %

## SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.  
Artificial respiration and/or oxygen may be necessary.  
Seek medical advice.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Wash clothing before reuse.  
Seek medical advice.
- In case of eye contact : Remove contact lenses.  
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Obtain medical attention.
- If swallowed : Rinse mouth with water.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Never give anything by mouth to an unconscious person.

# SAFETY DATA SHEET

## PURITY™ FG COMPRESSOR FLUID 46

000003000431



Version 2.0

Revision Date 2018/07/23

Print Date 2018/07/23

Seek medical advice.

Most important symptoms and effects, both acute and delayed : First aider needs to protect himself.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : No information available.
- Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray.
- Hazardous combustion products : Carbon oxides (CO, CO<sub>2</sub>), sulphur oxides (SO<sub>x</sub>), smoke and irritating vapours as products of incomplete combustion.
- Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Evacuate personnel to safe areas.  
Material can create slippery conditions.
- Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
- Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.  
Remove all sources of ignition.  
Soak up with inert absorbent material.  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Contact the proper local authorities.

---

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Use only with adequate ventilation.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin, eyes and clothing.  
Do not ingest.

# SAFETY DATA SHEET

## PURITY™ FG COMPRESSOR FLUID 46

000003000431



Version 2.0

Revision Date 2018/07/23

Print Date 2018/07/23

Keep away from heat and sources of ignition.  
Keep container closed when not in use.

Conditions for safe storage : Store in original container.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a dry, cool and well-ventilated place.  
Keep in properly labelled containers.  
To maintain product quality, do not store in heat or direct sunlight.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH

Engineering measures : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection  
Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

# SAFETY DATA SHEET

## PURITY™ FG COMPRESSOR FLUID 46

000003000431



Version 2.0

Revision Date 2018/07/23

Print Date 2018/07/23

- |                          |  |
|--------------------------|--|
| Skin and body protection | : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.                   |
| Protective measures      | : Wash contaminated clothing before re-use.  |
| Hygiene measures         | : Remove and wash contaminated clothing and gloves, including the inside, before re-use.<br>Wash face, hands and any exposed skin thoroughly after handling. |

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- |  |   |
|--|---|
| Appearance                             | : viscous liquid  |
| Colour                                 | : colourless  |
| Odour                                  | : Mild petroleum oil like.  |
| Odour Threshold                        | : No data available   |
| pH                                     | : No data available   |
| Pour point                             | : -45 °C (-49 °F)   |
| Boiling point/boiling range            | : No data available   |
| Flash point                            | : 240 °C (464 °F)<br>Method: Cleveland open cup                             |
| Fire Point                             | : No data available   |
| Auto-Ignition Temperature              | : No data available   |
| Evaporation rate                       | : No data available   |
| Flammability                           | : Low fire hazard. This material must be heated before ignition will occur. |
| Upper explosion limit                  | : No data available   |
| Lower explosion limit                  | : No data available   |
| Vapour pressure                        | : No data available   |
| Relative vapour density                | : No data available   |
| Relative density                       | : No data available   |
| Density                                | : 0.8686 kg/l (15 °C / 59 °F)   |
| Solubility(ies)                        |   |
| Water solubility                       | : insoluble   |
| Partition coefficient: n-octanol/water | : No data available   |
| Viscosity                              |   |

# SAFETY DATA SHEET

## PURITY™ FG COMPRESSOR FLUID 46

000003000431



Version 2.0

Revision Date 2018/07/23

Print Date 2018/07/23

Viscosity, kinematic	: 44.3 cSt (40 °C / 104 °F)
	6.6 cSt (100 °C / 212 °F)
Explosive properties	: Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

### SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reactions	: Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	: No data available
Incompatible materials	: Reactive with oxidising agents, acids and alkalis.
Hazardous decomposition products	: May release COx, NOx, SOx, SiOx, aldehydes, methacrylate monomers, smoke and irritating vapours when heated to decomposition.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Eye contact  
Ingestion  
Inhalation  
Skin contact

#### Acute toxicity

##### Product:

Acute oral toxicity	: Remarks: No data available
Acute inhalation toxicity	: Remarks: No data available
Acute dermal toxicity	: Remarks: No data available

##### Components:

##### **White mineral oil (petroleum):**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg,

# SAFETY DATA SHEET

## PURITY™ FG COMPRESSOR FLUID 46

000003000431



Version 2.0

Revision Date 2018/07/23

Print Date 2018/07/23

### Skin corrosion/irritation

#### Product:

Remarks: No data available

### Serious eye damage/eye irritation

#### Product:

Remarks: No data available

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

No data available

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae : Remarks: No data available

Toxicity to bacteria : Remarks: No data available

### Persistence and degradability

#### Product:

# SAFETY DATA SHEET

## PURITY™ FG COMPRESSOR FLUID 46

000003000431



Version 2.0

Revision Date 2018/07/23

Print Date 2018/07/23

Biodegradability : Remarks: No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### TDG

Not regulated as a dangerous good

Not applicable for product as supplied.

---

## SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

**The components of this product are reported in the following inventories:**



# SAFETY DATA SHEET

## PURITY™ FG COMPRESSOR FLUID 46

000003000431



Version 2.0

Revision Date 2018/07/23

Print Date 2018/07/23

### DSL TSCA

On the inventory, or in compliance with the inventory  
All chemical substances in this product are either listed on the  
TSCA Inventory or are in compliance with a TSCA Inventory  
exemption.

### IECSC

On the inventory, or in compliance with the inventory

## SECTION 16. OTHER INFORMATION

For Copy of SDS : Internet: [lubricants.petro-canada.com/sds](http://lubricants.petro-canada.com/sds)  
Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-4518  
Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-800-201-6285  
Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285  
For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2018/07/23

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.