



Units 1&2 Little Row, Fenton Industrial Estate. Stoke-on-Trent ST4 2SQ

Telephone: 01782 410381 Fax: 01782 410684

E-mail: sales@premierlubricants.co.uk.

TECHNICAL DATA SHEET

BLOCK GREASE

DESCRIPTION:

Hard smooth non-porous grease with good resistance to oxidation. Formulated from a soap thickened mineral oil Premier Block Grease exhibits only slight changes in consistency at elevated temperatures.

APPLICATIONS:

Premier Block Grease has been used successfully for several lubrication duties on many items of industrial plant and equipment. The product was developed primarily as a journal bearing grease.

BENEFITS:

Good resistance to pressure in heavily loaded applications
Malleable easy to work with – cut and shape.

TYPICAL PHYSICAL CHARACTERISTICS:

Appearance	Stiff grease stick
Colour	Dark brown
NLGI Classification	5 – 6
Drop Point	> 160°C
Flash Point	> 200°C

PACKAGING:

Grease Sticks – packed in boxes of 10Kg

Premier Lubricants Limited. Registration No. 6425371
Registered Address. PO Box 165 Winton House,
Stoke Road, Stoke-on-Trent ST4 2RN

Little Row, Fenton Industrial Estate
Stoke-on-Trent, Staffordshire ST4 2SQ
Telephone. 01782 410381 / 410389
Fax. 01782 410684
Email. sales@premierlubricants.co.uk
www.premierlubricants.co.uk