

WHITE GREASE (F402)

Description

PROTEAN White Grease is a NSF: H1 registered, spray-formulated, water resistant lubricant - ideal for use on roller and needle bearings and chains. Suitable for use within Food & Beverage, Packaging, Pharmaceutical and other cleanroom environments.

Outstanding Features

- · NSF: H1 registered
- · Effective to high temperatures
- · Water resistant suitable where frequent washing down of equipment occurs
- · Corrosion resistant
- Temperature range: -20°C to +200°C
- · 360° valve for inverted use

Directions for Use

- Store out of direct sunlight and below +50°C
- · Consult the safety data sheet prior to use
- · Shake aerosol well before use
- · Clean area to be sprayed of all dirt, grease, grime and water prior to use
- Spray evenly onto the surface from a distance of 20-30cm

Technical Data

Category H1 (lubricant with incidental food contact, for use

in and around food processing areas)

NSF Certificate No. 139270

Does not contain any genetically modified ingredients, nut oils or animal derivatives

Appearance White/creamy light grease

Odour Slightly sweet

Contents Blend of grease with pentane solvent and propane

/ butane / isobutane propellant

Flammability Extremely flammable

Storage Out of direct sunlight, below +50°C

Flash Point -60°C

Temperature range -20° to 65°C

Relative Density 0.74
Solubility in water Insoluble

Pack Sizes 12 x 400ml cans

The content of this data sheet is given in good faith but without warranty.



Compilation Date: 09/02/2016