

TECHNICAL DATA SHEET MULTI-LUBE (F404)

Description

PROTEAN Multi-Lube is a NSF: H1 registered general purpose food grade lubricant for use on cables, chains, castors, hinges, bearings and pins.

Suitable for use within Food & Beverage, Packaging, Pharmaceutical and other cleanroom environments.

Outstanding Features

- NSF: H1 registered
- · Effective over a wide temperature range
- · Good water displacement and penetration properties
- Effective corrosion resistance
- Temperature range: -20°C to +200°C
- · 360° valve for inverted use

Directions for Use

- Store out of direct sunlight and below +50°C
- · Consult the safety data sheet prior to use
- · Shake aerosol well before use
- · Once sprayed, allow the lubricant to thicken on before use
- Use the extension tube for greater accuracy.
- · Do not spray directly onto food

Technical Data

| Category | H1 registered (lubricant with incidental food contact, for use in and around food processing areas) |
|---------------------|---|
| NSF Certificate No. | 139271 |
| | Does not contain any genetically modified ingredients, nut oils or animal derivatives |
| Appearance | Off-white, light viscosity oil |
| Odour | Vegetable oil, barely perceptible |
| Contents | Blend of oils, propan-2-ol and propane / butane / isobutane propellant |
| Flammability | Extremely flammable |
| Storage | Below 50°C |
| Flash Point | >100°C |
| Temperature range | -20° to 200°C |
| Relative Density | 0.89 |
| Solubility | Insoluble in water |
| Pack Sizes | 12 x 400ml cans |







Unit 31, Kyle Road Industrial Estate Irvine, Ayrshire KA12 8LE. Tel: +44 (0) 1294 311 066 technical@tygrisindustrial.com

Compilation Date: 09/02/2017