

PROTEAN PTFE DRY FILM LUBRICANT F410

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: PROTEAN PTFE DRY FILM LUBRICANT

Article number: F410

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: TYGRIS Industrial

Unit 31

Kyle Road Industrial Estate

Irvine Ayrshire KA12 8LE

Tel +44 (0) 1294 311 066 Fax +44 (0) 1294 277 115

Email technical@tygrisindustrial.com

Further information obtainable from:

Technical Department

1.4 Emergency telephone number:

Tel +44 (0) 1294 311 066





PROTEAN PTFE DRY FILM LUBRICANT F410

2. Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; Aquatic Chronic 2: H411; STOT SE 3: H336; -: EUH066;

-: H229

Most important adverse

effects:

Repeated exposure may cause skin dryness or cracking. Extremely flammable aerosol. Pressurised container: May burst if heated. May cause drowsiness or

dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

EUH066: Repeated exposure may cause skin dryness or cracking. Hazard statements:

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Signal word: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50°C.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

3. Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PENTANE - REACH registered number(s): 01-2119459286-30

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|----------|-----------|--|---------|
| 203-692-4 | 109-66-0 | - | Flam. Liq. 2: H225; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411; -: EUH066 | 10-30% |

Compilation Date: 04/09/2018



PROTEAN PTFE DRY FILM LUBRICANT F410

4. First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult

a doctor. Move the exposed person to fresh air.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special

treatment:

Eye bathing equipment should be available on the premises.

5. Firefighting measures

5.1 Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water

spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent

contact with skin and eyes.



PROTEAN PTFE DRY FILM

LUBRICANT F410

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not

approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the

escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container

for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

7. Handling and storage

7.1 Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of

the area. Do not handle in a confined space. Avoid the formation or spread of

mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.



PROTEAN PTFE DRY FILM LUBRICANT F410

8. Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PENTANE

Workplace exposure limits:

Respirable dust:

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK | 1800 mg/m3 | - | - | - |

DNEL/PNEC Values

DNEL/PNEC: No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory equipment: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves. Chemically resistant gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Not applicable.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol
Colour: White

Odour: Characteristic odour

Solubility in water: Insoluble

Also soluble in: Most organic solvents

Flash point°C: -60
Relative density: 0.72

9.2. Other information

Other information: No data available.



PROTEAN PTFE DRY FILM LUBRICANT F410

10. Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

11. Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

PENTANE

| ORAL RAT LD50 >2000 mg/kg | |
|---------------------------|--|
|---------------------------|--|

Relevant hazards for product:

| Hazard | Route | Basis |
|----------------------|-------|-----------------------|
| STOT-single exposure | - | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.



PROTEAN PTFE DRY FILM LUBRICANT F410

12. Ecological information

12.1. Toxicity

Hazardous ingredients:

PENTANE

FISH 96H LC50 1-10 mg/l

12.2. Persistence and degradability

Persistence and degradability:

Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

13. Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company. Dispose of contents and container according to national regulations.

Recovery operations: Not applicable.

Disposal of packaging: Not applicable.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.



PROTEAN PTFE DRY FILM LUBRICANT F410

14. Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D
Transport category: 2

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical safety assessment

Chemical safety A chemical safety assessment has not been carried out for the substance or the

assessment: mixture by the supplier.

16. Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU)

No 2015/830.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H222: Extremely flammable aerosol. H225: Highly flammable liquid and vapour. H229: Pressurised container: May burst if heated H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all

inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.