



Description

NSF: H1 Registered fluid developed for the release of seized components, and suitable for use within Food & Beverage, Packaging, Pharmaceutical and other clean room environments.

PROTEAN Penetrating Oil is a food grade penetrating and release fluid with anti-corrosion properties which actively penetrates seized components. A residual lubricating film adheres to the released part, facilitating re-assembly and helping prevent further corrosion.

Effective over a wide temperature range, PROTEAN Penetrating Oil is supplied, as standard, with an all angle valve which allows use in an inverted position.

Outstanding Features

- NSF: H1 registered
- Powerful penetration through rust, scale and grime
- Leaves a corrosion resistant coating
- Temperature range -20°C to +250°C
- 360° valve for inverted use

Directions for Use

- Store out of direct sunlight and below +50°C
- Consult the safety data sheet prior to use
- Shake aerosol well before use
- Spray components to be released from a distance of 15-20cm
- Leave for a short while to penetrate before releasing the component

Technical Data

Category	H1 registered (lubricant with incidental food contact, for use in and around food processing areas)
NSF Certificate No.	139298
	Does not contain any genetically modified ingredients, nut oils or animal derivatives
Appearance	Clear, quickly collapsing foamy spray
Odour	Virtually odourless
Contents	Blend of non-toxic hydrocarbons and propane/butane propellant
Flammability	Extremely flammable aerosol
Storage	Below 50°C
Flash Point	-60°C
Temperature range	-20° to +250°C
Relative Density	0.85
Solubility	Insoluble in water
Pack Sizes	12 x 400ml cans



The content of this data sheet is given in good faith but without warranty.