

TYGRIS TECHNICAL DATA SHEET

Greases, Bulk Fluids and Oils

Food Area High Temp 2 Grease

CODE: **TF8204/8230**



A high temperature resistant food grade grease which contains PTFE anti wear and other additives. Suitable for use in bearings and on sliding surfaces, with resistance to a wide range of cleaning chemicals.

Benefits:

- InS approved for use on food areas
- Provides long term lubrication
- Resistant to high temperatures
- Carbon deposits are reduced
- High resistance to corrosive contaminants
- Good sealing properties
- PTFE lubricant adds anti wear performance
- Compatible with most seals

Technical Data:

Category:	H1 – Lubricants with incidental contact
NSF Certificate No:	148574
Appearance:	White semi-translucent grease
NLGI Classification:	2
Base Oil:	High viscosity silicone oil
Solid Lubricant:	PTFE
Thickener:	Inorganic thickener
Copper Corrosion:	Negative
Water Washout:	<2% maximum
Four Ball Weld Load:	180kg
Temperature range:	-20° to 220°C
dN Factor:	200,000
Melting Point:	>150°C
Relative Density:	0.99
Solubility:	Insoluble in water
Pack Sizes:	12 x 400gm cartridges or 3kg tin
Directions for Use:	Apply with a grease gun or by hand, taking care not to over-lubricate

