

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name:** STRIPELINE MARKING PAINT WHITE

**Article number:** LMW

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers.

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:** TYGRIS Industrial  
Unit 31  
Kyle Road Industrial Estate  
Irvine  
Ayshire  
KA12 8LE  
Tel +44 (0) 1294 311 066  
Fax +44 (0) 1294 277 115  
Email [technical@tygrisindustrial.com](mailto:technical@tygrisindustrial.com)

**Further information obtainable from:** Technical Department

**1.4 Emergency telephone number:** Tel +44 (0) 1294 311 066

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** STOT SE 3: H336; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Aerosol 1: H222; Lact.: H362; -: EUH208; -: H229

**Most important adverse effects:** Contains isodecylloxpropylamine acetate. May produce an allergic reaction. Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. May cause harm to breast-fed children. Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

**Hazard statements:** EUH208: Contains isodecylloxpropylamine acetate. May produce an allergic reaction.  
H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.  
H362: May cause harm to breast-fed children.  
H411: Toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS02: Flame  
GHS07: Exclamation mark  
GHS09: Environmental



**Signal word:** Danger

**Precautionary statements:** P102: Keep out of reach of children.  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211: Do not spray on an open flame or other ignition source.  
P251: Do not pierce or burn, even after use.  
P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P263: Avoid contact during pregnancy/while nursing.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50°C.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

### 3. Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous ingredients:

ACETONE - REACH registered number(s): 01-2119471330-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	30-50%

##### PROPANE

200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
-----------	---------	--	-------------------------------------	--------

##### BUTANE

203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	----------	--	-------------------------------------	-------

##### N-BUTYL ACETATE

204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---	--	-------

##### SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC.; LOW BOILING POINT NAPHTHA

265-199-0	64742-95-6	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; Aquatic Chronic 2: H411; STOT SE 3: H336; -: EUH066	1-10%
-----------	------------	---	---	-------

##### ISOBUTANE

200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	---------	--	-------------------------------------	-------

##### 1,2,4-TRIMETHYLBENZENE

202-436-9	95-63-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%
-----------	---------	---	---	-------

##### 1-METHOXY-2-PROPANOL

203-539-1	107-98-2	-	Flam. Liq. 3: H226; STOT SE 3: H336	1-10%
-----------	----------	---	-------------------------------------	-------

##### 2-BUTOXYETHANOL

203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%
-----------	----------	---	---	-------

**ETHYL ACETATE**

205-500-4	141-78-6	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---	---	-------

**ALKANES, C14-17, CHLORO**

287-477-0	85535-85-9	-	Lact.: H362; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	1-10%
-----------	------------	---	--	-------

**ISODECYLOXPROPYLAMINE ACETATE**

-	28701-67-9	-	Acute Tox. 4: H302; Skin Corr. 1B: H314; STOT SE 3: H335; Aquatic Chronic 1: H410; Skin Sens. 1: H317	<1%
---	------------	---	---	-----

## 4. First aid measures

### 4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Do not induce vomiting. Consult a doctor.
- Inhalation:** Move to fresh air in case of accidental inhalation of vapours.

### 4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** There may be mild irritation at the site of contact.
- Eye contact:** There may be irritation and redness.
- Ingestion:** There may be soreness and redness of the mouth and throat.
- Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.
- Delayed / immediate effects:** No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

- Immediate / special treatment:** Not applicable.

## 5. Firefighting measures

### 5.1 Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. If outside do not approach from downwind.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may produce sparks. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## 7. Handling and storage

### 7.1 Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Keep away from sources of ignition.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** PC9a: Coatings and paints, thinners, paint removers.

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Hazardous ingredients:

ACETONE

#### Workplace exposure limits:

#### Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	500ppm 1210mg/m <sup>3</sup>	1500ppm 3620mg/m <sup>3</sup>	-	-

PROPANE

UK	1800 mg/m <sup>3</sup>	7200 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

BUTANE

UK	1450 mg/m <sup>3</sup>	1810 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

N-BUTYL ACETATE

UK	724 mg/m <sup>3</sup>	966 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

ISOBUTANE

UK	2400 mg/m <sup>3</sup>	9600 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

1,2,4-TRIMETHYLBENZENE

UK	125 mg/m <sup>3</sup>	-	-	-
----	-----------------------	---	---	---

1-METHOXY-2-PROPANOL

UK	375 mg/m <sup>3</sup>	560 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

2-BUTOXYETHANOL

UK	25 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>	-	-
----	----------------------	----------------------	---	---

ETHYL ACETATE

UK	200 ppm	400 ppm	-	-
----	---------	---------	---	---

**DNEL/PNEC Values**
**Hazardous ingredients:**

ACETONE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	186mg/kg/day	Workers	Systemic
DNEL	Inhalation	2420mg/m <sup>3</sup>	Workers	Local
DNEL	Inhalation	1210mg/m <sup>3</sup>	Workers	Systemic
DNEL	Oral	62mg/kg/day	Consumers	Systemic
DNEL	Dermal	62mg/m <sup>3</sup>	Consumers	Systemic
DNEL	Inhalation	200mg/m <sup>3</sup>	Consumers	Systemic
PNEC	Fresh water	10.6mg/l	-	-
PNEC	Marine water	1.06mg/l	-	-
PNEC	Fresh water	Intermittent release	-	-
PNEC	Fresh water sediments	30.4 mg/kg	-	-
PNEC	Marine sediments	3.04mg/kg	-	-
PNEC	Soil (agricultural)	29.5mg/kg	-	-
PNEC	Microorganisms in sewage treatment	100mg/l	-	-

**8.2. Exposure controls**

<b>Engineering measures:</b>	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.
<b>Respiratory equipment:</b>	Respiratory protection not required.
<b>Hand protection:</b>	Chemically resistant gloves.
<b>Eye protection:</b>	Safety glasses. Ensure eye bath is to hand.
<b>Skin protection:</b>	Protective clothing.
<b>Environmental:</b>	Prevent from entering in public sewers or the immediate environment.

**9. Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

<b>State:</b>	Aerosol
<b>Colour:</b>	White
<b>Odour:</b>	Characteristic odour
<b>Solubility in water:</b>	Miscible
<b>Also soluble in:</b>	Most organic solvents
<b>Flash point°C:</b>	-60
<b>Relative density:</b>	1.00

**9.2. Other information**

<b>Other information:</b>	No data available.
---------------------------	--------------------

## 10. Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4. Conditions to avoid

**Conditions to avoid:** Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## 11. Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

##### ACETONE

DERMAL	RAT	LD50	>7400	mg/kg
DERMAL	RBT	LD50	2000	mg/kg
ORAL	RAT	LD50	5800	mg/kg
VAPOURS	RAT	4H LC50	76000	mg/l

##### N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

##### 1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

##### 1-METHOXY-2-PROPANOL

IVN	RAT	LD50	4200	mg/kg
ORL	MUS	LD50	11700	mg/kg
ORL	RAT	LDLO	3739	mg/kg

##### 2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

##### ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

#### Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

#### Symptoms / routes of exposure

- Skin contact:** There may be mild irritation at the site of contact.
- Eye contact:** There may be irritation and redness.
- Ingestion:** There may be soreness and redness of the mouth and throat.
- Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.
- Delayed / immediate effects:** No data available.
- Other information:** Not applicable.

## 12. Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

ACETONE

ALGAE	192H EC10	530	mg/l
Activated Sludge	30m EC10	1000	mg/l
DAPHNIA	48H EC50	8800	mg/l
Daphnia magna	192H EC10	2212	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	5540	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

### 12.4. Mobility in soil

**Mobility:** Soluble in water.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms.

## 13. Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Not applicable.

**Disposal of packaging:** Not applicable.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## 14. Transport information

### 14.1. UN number

UN number: UN1950

### 14.2. UN proper shipping name

Shipping name: AEROSOLS

### 14.3. Transport hazard class(es)

Transport class: 2

### 14.4. Packing group

### 14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

### 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

## 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical safety assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## 16. Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.  
EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.  
H220: Extremely flammable gas.  
H222: Extremely flammable aerosol.  
H225: Highly flammable liquid and vapour.  
H226: Flammable liquid and vapour.  
H229: Pressurised container: May burst if heated  
H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.  
H312: Harmful in contact with skin.  
H314: Causes severe skin burns and eye damage.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H332: Harmful if inhaled.  
H335: May cause respiratory irritation.  
H336: May cause drowsiness or dizziness.  
H362: May cause harm to breast-fed children.  
H410: Very toxic to aquatic life with long lasting effects.  
H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.