

# SOLVENT TOOL & ELECTRONICS CLEANER IS2

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SOLVENT TOOL & ELECTRONICS CLEANER

Article number: IS2

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product category:** Solvent cleaner

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: TYGRIS Industrial

Unit 31, Kyle Road Industrial Estate

Irvine Ayrshire KA12 8LE

Tel +44 (0) 1294 311 066 Fax +44 (0) 1294 277 115

Email technical@tygrisindustrial.com

Further information obtainable from:

**Technical Department** 

1.4 Emergency telephone

number:

Tel +44 (0) 1294 311 066





### SOLVENT TOOL & ELECTRONICS **CLEANER**

IS<sub>2</sub>

#### 2. Hazards identification

2.1. Classification of the substance or mixture

**Physical hazards:** Aerosol 1 - H222

**Health hazards:** Eye Irrit. 2 - H319, STOT SE 3 - H336

2.2. Label elements

Hazard statements: H222: Extremely flammable aerosol.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Signal word: Danger

**Precautionary statements:** P102: Keep out of reach of children.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211: Do not spray on an open flame or other ignition source. P251: Pressurized container: Do not pierce or burn, even after use.

P261: Avoid breathing vapour/spray.

P271: Use only outdoors or in a well-ventilated area.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337+313: If eye irritation persists: Get medical advice/attention.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

P501: Dispose of contents/container in accordance with local regulations.

Supplementary

P264: Wash contaminated skin thoroughly after handling.

precautionary statements: P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell. P403+233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Supplemental label

information:

H229: Pressurised container: May burst if heated

2.3. Other hazards



# SOLVENT TOOL & ELECTRONICS CLEANER IS2

#### 3. Composition/information on ingredients

#### 3.2. Mixtures

#### **Hazardous ingredients:**

PROPAN-2-OL

EC	CAS	Index number	CLP Classification	Percent
200-661-7	67-63-0	-	Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	60-100%
BUTANE				
203-448-7	106-97-8	-	Flam. Gas 1 - H220	5-10%
ISOBUTANE				
200-857-2	75-28-5	-	Flam. Gas 1 - H220	1-5%

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 4. First aid measures

#### 4.1. Description of first aid measures

**General information:** Move the exposed person to fresh air at once. Get medical attention if any

discomfort continues.

**Skin contact:** Wash the skin immediately with soap and water. Get medical attention if any

discomfort continues.

**Eye contact:** Make sure to remove any contact lenses from the eyes before rinsing. Promptly

wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at

least 15 minutes. Get medical attention if any discomfort continues.

Ingestion: DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large

amounts of milk or water to people not unconscious. Get medical attention if any

discomfort continues.

**Inhalation:** Move the exposed person to fresh air at once. When breathing is difficult, properly

trained personnel may assist affected person by administering oxygen. Keep the

affected person warm and at rest. Get prompt medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed





# SOLVENT TOOL & ELECTRONICS CLEANER IS2

#### 5. Firefighting measures

5.1 Extinguishing media

**Extinguishing media:** Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Aerosol cans may explode in a fire.

5.3. Advice for fire-fighters

Special fire fighting procedures:

Containers close to fire should be removed or cooled with water. Use water to

keep fire exposed containers cool and disperse vapours.

#### 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wear necessary protective equipment. Extinguish all ignition sources. Avoid

sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

#### 7. Handling and storage

#### 7.1 Precautions for safe handling

**Handling requirements:** Keep away from heat, sparks and open flame. Avoid spilling, skin and eye

contact. Ventilate well, avoid breathing vapours. Use approved respirator if air

contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)





## SOLVENT TOOL & ELECTRONICS CLEANER

IS<sub>2</sub>

#### 8. Exposure controls/personal protection

#### 8.1. Control parameters

#### Workplace exposure limits:

#### **BUTANE**

Long-term exposure limit (8-hour TWA)	Short-term exposure limit (15-minute)	
WEL 600 ppm, 1450 mg/m <sup>3</sup>	WEL 750 ppm, 1810 mg/m <sup>3</sup>	

#### PROPAN-2-OL

WEL 400 ppm, 999 mg/m <sup>3</sup>	WEL 500 ppm, 1250 mg/m <sup>3</sup>
TVEE 100 ppin, 000 mg/m	**EE 000 pp, 1200g/

#### WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

Protective equipment:





**Engineering measures:** Provide adequate general and local exhaust ventilation.

General protective and hygienic measures:

Respiratory protection:

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that

becomes contaminated. When using do not eat, drink or smoke.

general level exc

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical

cartridge protection with appropriate cartridge.

**Hand protection:** Use protective gloves.

**Eye protection:** Use approved safety goggles or face shield.

Other Protection: Wear appropriate clothing to prevent any possibility of liquid contact and repeated

or prolonged vapour contact.

#### 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State: Aerosol

Colourless.

Odour: Characteristic

**Solubility:** Slightly soluble in water

Flammability limits: Lower: 0.8 % Upper: 12.0 %

9.2. Other information





# SOLVENT TOOL & ELECTRONICS CLEANER

IS<sub>2</sub>

#### 10. Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

**Chemical stability:** Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and other sources of ignition. Avoid contact with: Strong

oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

#### 11. Toxicological information

#### 11.1. Information on toxicological effects

**Skin contact:** Prolonged or repeated exposure may cause severe irritation. Acts as a defatting

agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. May cause sensitisation by skin contact. Irritating to skin.

**Eye contact:** Irritating to eyes. May cause chemical eye burns.

**Inhalation:** May cause irritation to the respiratory system. Vapours may cause headache,

fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may

damage respiratory system.

**Ingestion:** May cause discomfort if swallowed. May cause stomach pain or vomiting.

Gastrointestinal symptoms, including upset stomach.

Route of entry: Inhalation. Skin and/or eye contact.

#### 12. Ecological information

12.1. Toxicity

**Ecotoxicity:** Dangerous for the environment if discharged into watercourses.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

#### 13. Disposal considerations

#### 13.1. Waste treatment methods

General information: Empty containers must not be burned because of explosion hazard. Dispose of

waste and residues in accordance with local authority requirements.





## SOLVENT TOOL & ELECTRONICS CLEANER

IS2

#### 14. Transport information

UN Number (ADR): 1950 UN Number (IMDG): 1950 UN Number (IATA): 1950

14.2 UN proper shipping name

Proper shipping name: AEROSOLS

14.3. Transport hazard class(es)

ADR/RID/ADN Class: 2, Class 2: Gases

ADR Label No. 2.1

IMDG Class: 2.1

ICAO Class/Division: 2.1

Transport labels:



14.4. Packing group

Packing group: Not applicable.

14.5 Environmental hazards

Marine pollutant: No

14.6 Special precautions for user

EmS: 2-13

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

#### 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Statutory Instruments:** The Aerosol Dispensers (Amendment) Regulations 2014 No.1130.

Guidance Notes: Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

**EU Legislation:** The Aerosol Dispensers Directive 1975/324 EEC.

Regulation (EC) No.1272/2008: The Classification, Labelling and Packaging of

substances and mixtures Regulations.

Regulation (EC) No. 1907/2006: The Registration, Evaluation, Authorisation and

Restriction of Chemicals Regulations (REACH).

2001/95/EC The General Product Safety Directive (GPSD).

Commission Regulation (EU) 2015/830: Requirements for the compilation of

safety data sheets (amending REACH).

Authorisations (Title VII Regulation 1907/2006): No specific authorisations are

noted for this product.

Restrictions (Title VIII Regulation 1907/2006): No specific restrictions of use are

noted for this product.

15.2. Safety, health and environmental regulations/legislation specific for the substance or mixture





# SOLVENT TOOL & ELECTRONICS CLEANER IS2

#### 16. Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU)

No 2015/830.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

**Legal disclaimer** The above information is believed to be correct but does not purport to be all

inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.