



Product Information:

MULTITRANS MTS 75W-90

HIGH PERFORMANCE FULLY SYNTHETIC GEAR OIL

Description

Multitrans MTS 75W-90 is an advanced, fully synthetic gear oil developed for use in automotive light-duty and heavy duty axles and heavy-duty non-synchronised manual transmissions. The product has high load carrying ability and will protect all critical components over a wide range of operating temperatures and workloads. Rapid circulation from cold will ensure essential component protection at start up and promote the potential for fuel economy. Multitrans MTS 75W-90 will also provide effective wear, rust and corrosion protection.

The extremely strong synthetic base fluid maintains lubricating film integrity under the toughest shock load conditions demonstrating superior performance over conventional mineral oils.

Features

- Outstanding frictional durability (reducing the potential for vibration)
- Strong EP protection
- High level of thermal and oxidation stability
- Protects copper components from corrosive attack

Applications

Multitrans MTS 75W-90 gear oil is designed and recommended for use in non-synchronised manual gearboxes, differentials and final drives, where a SAE 75W-90 lubricant, complying with one of the performance levels listed below, is specified.

Performance Level

API GL-5, API MT-1, SAE J2360, Scania STO 1:0, MIL-PRF-2105E

Physical Characteristics

Density @ 15.6°C	0.872
Viscosity @ 100°C, cSt.	15.82
Viscosity @ 40°C, cSt.	100.60
Viscosity Index	168
Flash Point (Closed) °C	170
Pour Point, °C	-51

Figures based on average production values.

(TDS Multitrans MTS 75W-90 – 160516 Issue 2)

