# according to Regulation (EC) No. 1907/2006 **ENDURATEX** TM/MC EP 150



Revision Date 2017/02/13 Print Date 2017/02/23 Version 4.1



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

: ENDURATEX TM/MC EP 150 Product name

Product code : ENT150IBC, ENT150P20, ENT150DRR, ENT150DRM,

ENT150DCT, ENT150, ENT150BLK

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the

Substance/Mixture

: ENDURATEX EP oils are heavy duty extreme pressure gear oils for use in enclosed industrial gear drives operating under normal, heavy, or shock loading conditions. They are also recommended for lubricating plain or anti-friction bearings running under heavy or shock loading conditions.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

Petro-Canada Europe Lubricants Limited

Wellington House, Starley Way

Birmingham International Park Solihull B37 7HB

United Kingdom

E-mail address of person

responsible for the SDS

: EUSDS@petrocanadalsp.com

#### 1.4 Emergency telephone number

Emergency telephone

number

Petro-Canada Lubricants Inc.: +1 905-403-5770; CHEMTREC Transport Emergency: 1-800-424-9300;

Poison Control Centre: Consult local telephone directory for

emergency number(s).

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

# 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Internet: lubricants.petro-canada.com/sds

™ Owned or used under license by Petro-Canada Lubricants

Inc.

# according to Regulation (EC) No. 1907/2006 **ENDURATEX** TM/MC EP 150





Revision Date 2017/02/13 Print Date 2017/02/23 Version 4.1

# **Additional Labelling:**

**EUH208** May produce an allergic reaction. **EUH210** Safety data sheet available on request.

Contains: Polysulfides, di-tert-Bu and Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)

#### 2.3 Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### **Hazardous components**

| Chemical name                      | CAS-No.             | Classification    | Concentration |
|------------------------------------|---------------------|-------------------|---------------|
|                                    | EC-No.              |                   |               |
|                                    | Registration number |                   |               |
| lubricating oils (petroleum), C15- | 72623-86-0          | Asp. Tox. 1; H304 | 20 - 30 %     |
| 30, hydrotreated neutral oil-based | 276-737-9           |                   |               |
|                                    | 01-2119474878-16-   |                   |               |
|                                    | 0001                |                   |               |
|                                    |                     |                   |               |

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

Internet: lubricants.petro-canada.com/sds

Page: 2 / 10

according to Regulation (EC) No. 1907/2006 **ENDURATEX** TM/MC EP 150





Print Date 2017/02/23

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice

# 4.2 Most important symptoms and effects, both acute and delayed

Risks : First aider needs to protect himself.

### 4.3 Indication of any immediate medical attention and special treatment needed

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: No information available.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Cool closed containers exposed to fire with water spray.

Hazardous combustion

products

: Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), asphyxiants, smoke and irritating vapours as products of incomplete combustion.

5.3 Advice for firefighters

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

Internet: lubricants.petro-canada.com/sds ™ Owned or used under license by Petro-Canada Lubricants Inc.

Page: 3 / 10

# according to Regulation (EC) No. 1907/2006 **ENDURATEX** TM/MC EP 150



Revision Date 2017/02/13 Print Date 2017/02/23 Version 4.1



Environmental precautions : Do not allow uncontrolled discharge of product into the

environment.

6.3 Methods and material for containment and cleaning up

: Prevent further leakage or spillage if safe to do so. Methods for cleaning up

> Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation.

Contact the proper local authorities.

6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Use only with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Advice on protection against

fire and explosion

: None known.

Hygiene measures : Remove and wash contaminated clothing and gloves,

including the inside, before re-use. Wash face, hands and any


exposed skin thoroughly after handling.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store

in heat or direct sunlight.





Page: 4 / 10

# according to Regulation (EC) No. 1907/2006 **ENDURATEX** TM/MC EP 150

#### 000003000427



Page: 5 / 10

Revision Date 2017/02/13 Print Date 2017/02/23 Version 4.1

#### 7.3 Specific end use(s)

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

### 8.2 Exposure controls

#### **Engineering measures**

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

# Personal protective equipment

: Wear face-shield and protective suit for abnormal processing Eye protection

problems.

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

> ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Protective measures : Wash contaminated clothing before re-use.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

**Appearance** : viscous liquid

Colour : amber

Odour : Mild petroleum oil like.

Internet: lubricants.petro-canada.com/sds

# according to Regulation (EC) No. 1907/2006 **ENDURATEX** TM/MC EP 150

# 000003000427



Revision Date 2017/02/13 Print Date 2017/02/23 Version 4.1

Odour Threshold No data available pΗ : No data available : -33 °C (-27 °F) Pour point

Boiling point/boiling range : No data available Flash point : 269 °C (516 °F)

Method: Cleveland open cup

Fire Point : No data available **Auto-Ignition Temperature** : No data available Evaporation rate : No data available

Flammability (solid, gas) : Low fire hazard. This material must be heated before ignition

will occur.

: No data available Upper explosion limit : No data available Lower explosion limit : No data available Vapour pressure

Relative vapour density

No data available

Density : 0.882 kg/l (15 °C / 59 °F)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, kinematic : 150.0 cSt (40 °C / 104 °F)

15.0 cSt (100 °C / 212 °F)

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

#### 9.2 Other information

No data available

Internet: lubricants.petro-canada.com/sds ™ Owned or used under license by Petro-Canada Lubricants Inc.

# according to Regulation (EC) No. 1907/2006 **ENDURATEX** TM/MC EP 150



Revision Date 2017/02/13 Print Date 2017/02/23 Version 4.1

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

# 10.2 Chemical stability

# 10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

Stable under normal conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents, acids and alkalis.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: May release COx, NOx, SOx, H2S, SiOx, methacrylate monomers, aldehydes, alkyl mercaptans, sulfides,

asphyxiants, smoke and irritating vapours when heated to

decomposition.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

Information on likely routes of : Eye contact

exposure

Ingestion

Inhalation Skin contact

# **Acute toxicity**

**Product:** 

: Remarks: No data available Acute oral toxicity

: Remarks: No data available Acute inhalation toxicity

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No data available

### **Components:**

lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Internet: lubricants.petro-canada.com/sds

™ Owned or used under license by Petro-Canada Lubricants

Inc.

Page: 7 / 10

# according to Regulation (EC) No. 1907/2006 **ENDURATEX** TM/MC EP 150





Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Skin corrosion/irritation

**Product:** 

Remarks: No data available

Serious eye damage/eye irritation

**Product:** 

Remarks: No data available

# **SECTION 12: Ecological information**

# 12.1 Toxicity

**Product:** 

: Remarks: No data available Toxicity to fish

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae : Remarks: No data available

Toxicity to bacteria

Remarks: No data available

12.2 Persistence and degradability

**Product:** 

Biodegradability : Remarks: No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

Internet: lubricants.petro-canada.com/sds

™ Owned or used under license by Petro-Canada Lubricants

Inc.



Page: 8 / 10

# according to Regulation (EC) No. 1907/2006 **ENDURATEX** TM/MC EP 150



Revision Date 2017/02/13 Print Date 2017/02/23 Version 4.1



# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

### **SECTION 14: Transport information**

# International Regulations

#### **IATA-DGR**

Not regulated as a dangerous good

### **IMDG-Code**

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

ADR: Not Regulated ADN: Not Regulated RID: Not Regulated

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water contaminating class

(Germany)

: WGK 1 slightly water endangering

#### The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

**TSCA** : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

**IECSC** : On the inventory, or in compliance with the inventory

Internet: lubricants.petro-canada.com/sds

Page: 9 / 10

™ Owned or used under license by Petro-Canada Lubricants Inc.

according to Regulation (EC) No. 1907/2006 **ENDURATEX** TM/MC EP 150



Page: 10 / 10

#### 000003000427

Revision Date 2017/02/13 Print Date 2017/02/23 Version 4.1

**EINECS** : On the inventory, or in compliance with the inventory

#### 15.2 Chemical safety assessment

#### **SECTION 16: Other information**

**Full text of H-Statements** 

H304 : May be fatal if swallowed and enters airways.

Full text of other abbreviations

Asp. Tox. : Aspiration hazard

**Further information** 

For Copy of SDS : Internet: lubricants.petro-canada.com/sds

Europe, telephone: 00-800-7387-6000

For Product Safety Information: 1 905-804-4752

Prepared by : Product Safety: +1 905-804-4752

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.