

Description

High strength contact adhesive in non-chlorinated form. An easy to use, repositionable adhesive for bonding most surfaces, including textile, foam, rubber, plastic, foil, cardboard and paper. Good for fixing down carpets, underlay and floor tiles. In a non-chlorinated form for maximum safety.

Benefits & Features

- Strong, repositionable adhesion
- Fast drying
- Bonds most surfaces
- Variable discharge fan nozzle
- High strength bond

Directions for Use

Ensure surfaces are clean and dry. Shake can well before use. Spray a number of light coats. For maximum adhesion, cover both surfaces. Allow a few moments for solvent to evaporate, then press surfaces together firmly, working out from the centre. Clean off excess adhesive with a solvent. When finished, invert can and spray briefly to clear the nozzle. **Do not use when surface temperatures will exceed 50°C. Not for use on plasticised PVC. Use only in well-ventilated areas.**

Technical Data

Appearance:	Yellowish fan of rapidly drying product
Odour:	Typical glue/solvent odour
Contents:	Blend of styrene butadiene polymer and supplementary additives in heptanes, acetone and butanone with butane/propane propellant
Storage:	Below 50°C
Flash Point:	<0°C
Relative Density:	0.85
Solubility:	Insoluble in water
Temperature Range:	Up to 50°C maximum surface temperature

Please Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

