

Product Information:

LOCOMAX 20W-40 ZF RAILROAD DIESEL ENGINE OIL



Description:

Locomax 20W-40 ZF is a Zinc and Chlorine-free oil designed for medium speed railroad diesel engines. This product is manufactured from severely refined mineral base oils and specially selected performance additives.

Applications

Locomax ZF 20W-40 ZF is blended to comply with the performance levels specified by the Locomotive Maintenance Officers Association (LMOA) for Generations 4, 5 and 6. It also fulfils the requirements of API CF.

Performance Levels

API CF

LMOA Generation 6 Approval

G.E. Generation 4 Long Life

EMD Approval (567, 645, 710 engines, EPA Tier 3 and previous emission standards)

Physical Characteristics

| SAE Grade | 20W-40 |
|-----------------------------------|--------------|
| Appearance | Amber liquid |
| Relative Density @ 15.6 °C | 0.879 |
| Kinematic Viscosity @ 40°C (cSt) | 120.1 |
| Kinematic Viscosity @ 100°C (cSt) | 15.4 |
| Viscosity Index | 120 |
| CCS @ -15°C (mPa.s) | 9500 maximum |
| Closed Flash Point (°C) | 226 |
| BN (mgKOH/g) | 9 |

Figures based on average production values

Part No.S: TBA

(TDS Locomax 20W-40 ZF – 190318 Issue 2)

